

QUANTUM X™ TECHNOLOGY

HEAVY COMMERCIAL USE

foot traffic.

dents strengthened by real diamonds

Industry-leading resistance to scratches, stains, and

INDENT RESISTANT

Durable enough to withstand heavy everyday





































BRIGHTON AT-16



PALOMINO AT-26









PET FRIENDLY

WATERPROOF

FIRE RESISTANT

Installation	PLANK SIZE	OVERALL THICKNESS	WEAR LAYER
Float, Glue Down	7.2"x48"	5mm	20mil with QXT
PLANKS/BOX	SQ FT/Box	BOXES/PALLET	SQ FT/PALLET
10	24.028	55	1321.54
Indent/Scratch Resistance	TEMPERATURE RANGE		LINEAR FEET BEFORE TRANSITION NEEDED
1162 PSI	Do not install below 50°. 24-hr acclimation needed		50













QUANTUM X™ TECHNOLOGY

Industry-leading resistance to scratches, stains, and dents strengthened by real diamonds.



WATERPROOF



INDENT RESISTANT



FIRE RESISTANT



ANTI-MICROBIAL



PET FRIENDLY



ZERO VOCS

specifications

Installation	Plank Size	OVERALL THICKNESS	WEAR LAYER
Float, Glue Down	7"×48"	4.7mm	12mil with QXT
PLANKS/BOX	SQ FT/Box	BOXES/PALLET	SQ FT/PALLET
12	28.365	50	1418.25
Indent/Scratch Resistance	TEMPERATURE RANGE		LINEAR FEET BEFORE TRANSITION NEEDED
1162 PSI	Do not install below 50°. 24-hr acclimation needed		50

































SIZE MATTERS WITH V-EVO® XL

The result of years of innovation, V-EVO® XL series Premium Engineered Stone Polymer Composite (ESPC) flooring boasts the lowest defect rate in the industry. Advances such as our Quantum X^{∞} Wear Layer, provide industry-leading protection against scratches, stains, and dents, while the AuthenTex $^{\infty}$ finish on the extra large planks provides a luxurious upscale feel.



LARGE AND LUXURIOUS

Ultra-long and extra- wide planks provide an upscale look, and are 89% larger than a standard 7"x48" plank.



AUTHENTEX™ FINISH

High definition imagery plus an Embossed In Register creates an authentic wood look and texture.



QUANTUM X™ TECHNOLOGY

Industry-leading resistance to scratches, stains, and dents strengthened by real diamonds.



CLIMATEGUARD™ RESISTANCE

Resists extreme temperatures, allowing product to be used in 3-season rooms such as cabins and enclosed patios.



HEAVY COMMERCIAL USE

Durable enough to withstand heavy everyday foot traffic.



WATERPROOF







INDENT RESISTANT



ANTI-MICROBIAL



ZERO VOCS

SPECIFICATIONS

Installation	PLANK SIZE	OVERALL THICKNESS	WEAR LAYER
Float, Glue Down	8.97"×70.86"	7mm	20mil with QXT
PLANKS/BOX	SQ FT/Box	Boxes/Pallet	SQ FT/PALLET
4	17.67	52	918.84
Indent/Scratch Resistance	TEMPERATURE RANGE	LINEAR FEET BEFORE TRANSITION NEEDED	EDGE
2200 PSI	-19° to +176°	200	Painted Bevel











MAPLE XL-05



















